





# Scanning Stage SCAN IM 120 x 88 for BX 51 / 61 WI

## **Specification**

Travel range:: max. 120 x 88 mm

Repeatability: < 1 µm

measured according to VDI / DGQ 3441

Accuracy: +/- 3 µm\*

measured according to VDI / DGQ 3441

Orthogonality: < 40 sec., typically < 15 - 20 sec.

Resolution: 0,05 \mum^\* (smallest step size)

Max. travel speed: 60 mm/s\*, with 1 mm lead screw pitch

Motor: 2-phase stepper motor

Material: aluminium

Limit switches: mechanical limit switches

Weight: 4.300 g

Surface: anodic coating, black lacquering

Certification: DIN EN ISO 9001 : 2000

Packaging Type: protective polyurethane foam

Packaging size / weight: 66 x 56 x 36 cm / 12 kg

## **Oder Information**

Part No.: 00-24-558-0000, with 1 mm lead screw pitch

### **Features**

 exchangeable stage inserts for different kinds of applications

### **Accessories**

Stage insert for slide 76 x 25 mm (3" x 1")

Part No.: 00-29-411-8010

Universal stage insert Part No.: 00-29-411-8150

Tel: 0755-84870203 E-mail: sales@highlightoptics.com www.highlightoptics.com

<sup>\*</sup> Specifications valid with Märzhäuser stage controller only

Specifications subject to change without notice.