



电话: 0755-84870203

邮箱: sales@highlightoptics.com



Scanning Stage SCAN IM 80 x 55 for Olympus BX 45

Travel range: 80 x 55 mm (3,15" x 2,15")

Repeatability: < 1 µm

(bi-directional, measured according to VDI / DGQ 3441)

Accuracy: +/- 3 µm (measured according to VDI / DGQ 3441)

 $\begin{tabular}{ll} Resolution: & 0,01 \ \mu m \ (smallest \ step \ size) \end{tabular}$

Orthogonality: < 10 arc sec

Motor: 2-phase stepper motor

Max. travel speed: 60 mm/s, with 1 mm ball screw pitch

120 mm/s, with 2 mm ball screw pitch

Limit switches: mechanical limit switches

Material: aluminium

Surface: anodic coating, black laquered

Weight: 4,300 g

Dimensions:

Order Information

Order No.: 00-24-440-0000, 1 mm ball screw pitch Order No.: 00-24-441-0000, 2 mm ball screw pitch

Product Features

- exchangeable stage inserts for different kinds of applications
- 5 years guarantee, if the scanning stage is operated in the system with the Märzhäuser TANGO controller!

Accessories

Stage insert for 2 slides 3" x 1" (included in delivery)

Order No.: 00-24-440-1000

