



海纳光学


电话: 0755-84870203


邮箱: sales@highlightoptics.com

Kaleo MultiWAVE

multi-wavelength,
large dynamic range
interferometer

PHASICS
the phase control company






Interferometric solution for filters and coated optics testing at dedicated wavelengths

PHASICS is innovating in optical metrology with a new instrument able to measure both transmitted and reflected wavefront error (TWE/ RWE). Coated and uncoated optics can be qualified over a diameter of 5.1 inches (130 mm) at their working wavelengths.

Kaleo MultiWAVE is an advantageous alternative and cost-effective solution to the purchase of several interferometers. The system offers a **measurement accuracy comparable to Fizeau interferometry**.

Kaleo MultiWAVE works at different wavelengths to perform qualification of optics and coatings at their working wavelengths.



HIGH DYNAMIC RANGE





MEASUREMENT OF LARGE ABERRATIONS

- More than 20λ of aberration can be measured with Kaleo MultiWAVE
- More dynamic range than a classical Fizeau interferometer

RWE of 5" wide band pass filter at 653nm

APPLICATIONS

- Coated optics and filters testing at real operating wavelengths
- High dynamics surface testing



ACHROMATIC SYSTEM

1 Same results at any wavelength

2 The instrument can be used at any wavelength to match the sample's operating wavelength

KEY FEATURES



Up to 8 wavelengths



High dynamic range



WFE & MTF measurement




Insensitive to vibration



Compatible with MetroPro & ISO

RESULTS SIMILAR TO FIZEAU INTERFEROMETRY



SYSTEM

Configuration	Double pass
Measurement capability	RWE of reflective surfaces TWE of transparent optics
Number of wavelengths per instrument	1 or 2 (standard), up to 8 (custom)
Custom wavelengths	Any wavelength from 193 nm to 14 μ m Including: UV: 266, 355, 405 nm VIS / NIR: 550, 625, 780, 940, 1050 nm SWIR / MWIR / LWIR: 1.55, 2.0, 3.39, 10.6 μ m
Clear aperture	5.1" (130 mm)
Beam height	108 mm
Alignment system	Live phase & Zernike coefficients display
Polarization	Compatible with depolarizing optics
Alignment FOV	+/- 2°
Pupil focus range	+/- 2.5 m
Dimensions	910 x 600 x 260 mm, 25 kg
Vibration isolation	Not necessary

PERFORMANCE⁽¹⁾

RMS repeatability ⁽²⁾	< 0.7 nm (< λ / 900)
Accuracy	80 nm PV ⁽³⁾
Dynamic range (defocus)	500 fringes (SFE = 150 μ m)
Sample reflectivity range	~4% - 100%

(1) On a 4" pupil size, with a 625 nm source

(2) 36 sequential measurements are performed on a 4" reference mirror, each being averaged 16 times. A reference is defined as the average of all odd numbered measurements. RMS repeatability is then defined as the average RMS difference plus 2 times the standard deviation of the difference between even numbered measurements and the reference.

(3) For a 1 μ m PV defocus

MARKETS




Optics & Filters
manufacturers



Space &
Defense



Automotive



PHASICS
the phase control company



海纳光学

电话: 0755-84870203

邮箱: sales@highlightoptics.com