



# SID4 LWIR-640 (8-14 μm)

## WAVE FRONT SENSOR



→ PHASICS introduces an **ultra high resolution wave front sensor** for long wavelength IR region (from 8 μm to 14 μm).

For **laser beam metrology** (CO<sub>2</sub> laser, LWIR OPO laser sources), the SID4 LWIR-640 gives an exhaustive beam characterization (aberrations, M<sup>2</sup>, intensity profiles, beam parameters).


For **optical metrology**, the SID4 LWIR-640 is the perfect tool to characterize IR objectives (thermal imaging, security & safety vision) or IR lenses (for CO<sub>2</sub> laser) giving you aberrations, surface quality, PSF, MTF and focal length.

### ↓ SPECIFICATIONS

Aperture dimension	16 x 12 mm <sup>2</sup>
Spatial resolution	100 μm
Sampling	160 x 120
Wavelength range	8 - 14 μm
Accuracy (Absolute/Relative mode)	75 nm RMS / 25 nm RMS
Sensitivity	25 nm RMS
Analysis rate	> 10 fps
Acquisition rate	40 fps
Dimensions (WxHxL)	96 x 110 x 90 mm
Weight	850 g

### ↘ KEY FEATURES

- High resolution (160 x 120)
- Absolute measurement
- Broadband
- High numerical aperture measurement for analysis without any additional relay lens
- Fast measurement
- Insensitive to vibration
- Cost effective



**海纳光学**

电话：0755-84870203

邮箱：[sales@highlightoptics.com](mailto:sales@highlightoptics.com)